

LONG RUN ENERGY

A petrol generator designed specifically for intensive operations where performance power is demanded by professional user, over an extended period of time.

Standard Equipment

Starting system Recoil

Main Features

Frequency	Hz	50
Voltage	V	230
Power factor	cos ϕ	0.9
Phase and connection		1

Power Rating

Standby power LTP	kVA	2.9
Standby power LTP	kW	2.6
Continuous power COP	kVA	2.5
Continuous power COP	kW	2.2

Ratings definition (According to standard ISO8528 1:2005)**COP** - Continuous Power:

It is defined as being the maximum power which a generating set is capable of delivering continuously for an unlimited number of hours, with the maintenance intervals and procedures being carried out as prescribed by the manufacturers.

LTP - Limited-Time running Power:

It is defined as the maximum power available, under the agreed operating conditions, for which the generating set is capable of delivering for up to 500 h of operation per year (whose no more than 300 for continuative use) with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. No overload capability is available.

Engine Specifications

Brand	Honda	
Model	GX160	
Engine cooling system	Air	
Displacement	cm ³	163
Aspiration	Natural	
Speed governor	Mechanical	
Operating Speed-Nominal	rpm	3000
Oil capacity	L	0.6
Fuel	Gasoline	
Starting system	Recoil	
Fuel consumption @ 75% PRP	L/h	0.88


Alternator Specifications

Class	H	
IP protection	23	
Poles	2	
Voltage tolerance	%	+5; -10 (cosφ1)

Dimensional data

Length	(L) mm	623
Width	(W) mm	409
Height	(H) mm	500
Dry weight	kg	41
Fuel tank capacity	L	11

Autonomy

Running time @ 75% PRP	h	12.50
------------------------	---	-------

Noise level

Guaranteed noise level (LWA)	db(A)	96
Noise pressure level @ 7 mt	db(A)	68

GENSET CONTROL

COMMANDS:

- Selector switch: OFF - ON
- Starting systems: Recoil
- Fuel Cock

PROTECTIONS STANDARD:

- Thermal protection
- Oil Guard

SOCKET TYPE

SCHUKO 230V 16A IP54

2



SUPPLEMENTS CONTROL (Available when ordered)

ASCODIF

Extra Protection with:

- differential protection 30mA
- circuit breake – hourmeter



ACCESSORIES

TRANSPORTATION KIT

with fix handles



TRANSPORTATION KIT

with folding handles



LIGHT TOWER

for portable generators (with tubular frames)

- Maximum Height 4.2m
- Elevations Pneumatic
- Quick open/close systems for legs
- Mast support and four lifting
- Lamp available Watt/Type:
 - n.4 X 500W Halogen (required power from generator: 2.5kVA 230V Single Phase)
 - n.4 X 1000W Halogen (required power from generator: 5,0kVA 230V Single Phase)



MTS- MANUAL TRANSFER SWITCH

Manual transfer switch 40A (for manual control versions 230V)



Publishing date: 22/11/13

©2012 | PR INDUSTRIAL s.r.l. | All rights reserved | Image shown may not reflect actual package. Specifications subject to change without notice | ENERGY GENERATION is registered trademarks of PR INDUSTRIAL s.r.l. Other company, product or service names may be trademarks or service marks of others. RevA (06/2012).